

100 Gbit/s VCSEL (880 nm)


Contact type: GSG

Product Code:

V50-880-GSG-C1 1x1

V50-880-GSG-C4 4x1

Engineering Samples
Preliminary datasheet



Product Description

These compact and very high modulation rate top-emitting GaAs-based vertical cavity surface emitting laser (VCSEL) chips are available as engineering samples for use in the development and evaluation of optical interconnections, optical backplanes and integrated waveguides, and next-generation optical data communications systems. The VCSELs are contacted on the top-surface individually using ground-source-ground (GSG) microprobes or wire bonds.

Optical aperture: ~5-7µm

Features

- Up to 112 Gbit/s (PAM-4 modulation)
- Single chip size 250 x 250 µm
- Suitable for wire bonding

Applications


- 200G / 400G in SWDM
- Proprietary optical interconnects
- Active Optical Cables (AOC)

Parameter	Typical	Notes
Emission wavelength	880 nm	(range 870 – 890 nm)
Data rate	Up to 112 Gbit/s	56 GBaud/s PAM-4
Threshold current	< 0.6 mA	
Peak output power	4 mW	


Electro-Optical Specifications (T = 0 to 85°C)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Emission wavelength	λ		870		890	nm
Data rate	BR	PAM-4		50	56	GBaud/s
Optical bandwidth	BW (f3dBo)	6 mA		25	30	GHz
Slope efficiency	η	5-10 mA		0.5	0.6	W/A
Threshold current	I_{th}			0.5		mA
Differential resistance	R_d	5-10 mA		50	60	Ω
Beam divergence	Θ	$1/e^2$		30		$^\circ$
Peak output power	P_{max}			4		mW
Spectral bandwidth (RMS)	$\Delta\lambda_{RMS}$			0.6	0.65	nm


LIV Characteristics



Optical Spectrum




Frequency response (optical) at 25°C



Measurement of 13 chips across the wafer


Frequency response (optical) at 85°C



Measurement of 13 chips across the wafer


Test Equipment: Keysight VNA

V50-880-GSG-C4 Array dimensions



Qualification Notification

The VM100-880-GSG-Cxx has been tested to meet specifications outlined in this data sheet at room temperature. However, it has not undergone full qualification testing or characterization and therefore may not meet the performance specifications over all extremes.



VI Systems GmbH
Hardenbergstrasse 7
10623 Berlin
Tel.: +49 30 3083143 30
Fax: +49 30 3083143 59
sales@v-i-systems.com
www.v-i-systems.com